



LEGEND

HPG	High pressure gauge
LPG	Low pressure gauge
MW	Water pressure gauge
RM	Manual water filling cap
SFAS	Tank manual air vent
SFA	Manual air vent
VSCS	Tank water drain valve
SFAF	Free cooling manual air vent
VSCF	Free cooling water drain valve
ATS	Spring type antivibrant mounting (Opt)
ATV	Rubber type antivibrant mounting (Opt)

LIFTING AND CARRIAGE PRECAUTIONS

- Check the weight on the CE label to select appropriate lift equipment .
- Before lifting the unit make sure that the external panel is firmly fixed in place.
- To use only lifting points provided.
- The chains or slings must be of equal length.
- To use a spread-bar to avoid damage to the unit.
- The movement must be performed with caution and avoid abrupt movements.
- Never move the unit on rollers.
- Never lift the unit using a fork-lift.



Scala-Scale	Data-Date	23/01/14	Dis.to-Drawn	B.C.	N°Pezzi
Peso-Weight Kg.	Materiali-Materials				
Denominazione-Denomination WATER CHILLER mod. ENRF.160÷185/CS.ST.T.WP					
Particolare-Detail OVERALL DIMENSIONS - LIFT INSTRUCTIONS					
REFRIGERANT R410a					

MOD.	EMPTY WEIGHT	OPERATING WEIGHT
ENRF.160	1910 kg	2515 kg
ENRF.185	2000 kg	2670 kg

HITEMA	
DIS.-DRAW N.	DIM-ENRF-160ST0100
Rev.	02 - B.C. - 12/01/17
PROGRAM.N.	