

**Air-cooled liquid chillers ENR series, rotary / scroll compressors, R410A / R32 / R454B refrigerant, brazed plate / coaxial / shell and tube evaporator, condenser coil with copper tubes and aluminium fins, AC axial fans. IP54 protection rating, chillers suitable for outdoor installation. Inbuilt water storage tank and single pump P3 as standard. 60Hz version as option.**

Type of available evaporators: CX = HITEMA coaxial evaporator, convoluted tube in tube exchanger installed inside the water storage tank ST = shell and tube evaporator, with high thickness copper tubes (0,41mm) B-ES = stainless steel brazed plate evaporator	Type of available expansion elements CP = Capillary tube VTS = Thermostatic expansion valve ETS = Electronic expansion valve (available as option)
--	---

**TECHNICAL DATA**

<b>PERFORMANCES</b>		Model	001	002	003	004	005	006	008	010
NOMINAL COOLING CAPACITY	W12°C/7°C @ 35°C (1)	kW	1,6	2,1	3,9	4,7	5,6	6,3	7,9	9,3
TOTAL NOMINAL ABSORBED POWER		kW	1,1	1,4	1,8	2,1	2,4	2,8	3,7	4,6
EER		kW/kW	2,81	2,59	3,21	3,16	3,08	2,87	2,80	2,57
SEPR (HT) (3)		-	4,69	4,61	4,61	4,61	4,61	4,61	4,57	4,63
NOMINAL WATER FLOW		m3/h	0,3	0,4	0,7	0,8	1,0	1,1	1,4	1,6
MECHANICAL MODE PRESSURE DROPS (4) (5) (6)		kPa	20	22	20	23	23	37	26	25
<b>FRIGORIFIC SECTION</b>										
COMPRESSORS / REFRIGERATING CIRCUITS / PARTITION STEP	nr.	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1
KIND OF COMPRESSOR	-	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	SCROLL	SCROLL
KIND OF EVAPORATOR	-	B-ES	B-ES	B-ES	B-ES	B-ES	B-ES	B-ES	CX	CX
KIND OF EXPANSION ELEMENT	-	CP	CP	CP	CP	CP	CP	CP	VTS	VTS
<b>HYDRAULIC SECTION</b>										
WATER FLOW RANGE (6)	m3/h	0,3÷2,0	0,3÷2,0	0,6÷2,2	0,6÷2,2	0,8÷2,2	0,8÷2,2	1,2÷3,0	1,4÷3,0	1,4÷3,0
MAXIMUM PUMP ABSORBED POWER (WP OR OPTION DP)	P3 (2)	kW	0,56	0,56	0,56	0,56	0,56	0,56	0,88	0,98
MAXIMUM PUMP ABSORBED CURRENT (WP OR OPTION DP)		A	3,46	3,46	3,46	3,46	3,46	3,46	1,65	1,78
MAXIMUM PUMP ABSORBED POWER (OPTION PH OR DPH)	P5 (2)	kW	NA	NA	0,74	0,74	0,74	0,74	1,10	1,10
MAXIMUM PUMP ABSORBED CURRENT (OPTION PH OR DPH)		A	NA	NA	3,22	3,22	3,22	3,22	2,17	2,17
HYDRAULIC CONNECTIONS (THREADED / FLANGED)	BSP / DN	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1"	1"	
TANK VOLUME (5) (8)	dm³	10	10	25	25	25	25	50	50	
EXPANSION VESSEL VOLUME (OPTION XV) (9)	liters	NA	NA	NA	NA	NA	NA	5	5	
<b>FAN SECTION (AXIAL)</b>										
FANS	nr.	1	1	1	1	1	1	1	1	1
FAN SPEED REGULATION	-	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF
MAXIMUM FANS ABSORBED POWER	AC	kW	0,07	0,11	0,10	0,10	0,10	0,10	0,25	0,25
MAXIMUM FANS ABSORBED CURRENT		A	0,40	0,80	0,50	0,50	0,50	0,50	1,10	1,10
TOTAL AIR FLOW	m3/h	700	650	1800	1800	1580	1580	4100	4100	
<b>TOTAL ELECTRIC DATA</b>										
ELECTRICAL FEED	V/ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	400/3/50/N	400/3/50/N	
MAXIMUM ABSORBED CURRENT (F.L.A) (6)	A	6,1	7,5	10,8	12,4	14,4	16,7	10,2	10,5	
MAXIMUM PEAK CURRENT (L.R.A) (6)	A	16,0	21,0	27,5	39,5	46,5	57,5	50,0	50,0	
MAXIMUM PEAK CURRENT WITH SOFT START (OPTION SF) (L.R.A) (6)	A	NA	NA	NA	NA	NA	NA	NA	NA	
<b>NOISE DATA</b>										
SOUND PRESSURE FOR STANDARD CONFIGURATION (6) (7)	dB(A)	50,0	50,0	50,3	51,6	53,0	54,7	51,4	51,4	
SOUND PRESSURE FOR LOW NOISE CONFIGURATION (OPTION LNJ) (6) (7)	dB(A)	NA	NA	NA	NA	NA	NA	NA	NA	
<b>DIMENSIONS AND WEIGHT</b>										
LENGTH	mm	445	445	600	600	600	600	820	820	
WIDTH	mm	440	440	725	725	725	725	615	615	
HEIGHT	mm	806	806	1060	1060	1060	1060	1415	1415	
WEIGHT EMPTY FOR STANDARD CONFIGURATION (5) (6)	kg	55	55	90	95	95	100	160	165	
WEIGHT OPERATIVE FOR STANDARD CONFIGURATION (5) (6)	kg	65	65	115	120	120	125	210	215	

The manufacturer reserves the right to modify specifications without notice.

Last update: 27/01/2021  
Revision: 01-2021

Data referred to:

- (1) Data referred to inlet/outlet water temperature = +12/+7 °C, ambient temperature = +35°C, fluid = Water
- (2) Available pressure can be calculated from Hitema Online Selection Software
- (3) SEPR: data comply with the European Regulation (EU) 2016/2281, referring to high temperature process chillers
- (4) Pressure drops taken in account: evaporator, valves, piping
- (5) Data referred to standard chiller configuration as indicated in frigorific section, with different evaporator this data can change
- (6) Data referred to standard chiller configuration WP (single pump P3) and AC fans
- (7) Sound pressure level referred to measures according to normative ISO3744, pressure level at distance of 10 m, referred to free field on reflecting surface
- (8) To avoid excessive start/stop of the compressors a minimum water volume for the entire plant must be guarantee, the tank supplied by Hitema can be not enough
- (9) The expansion vessel volume is calculated considering 40°C of deltaT between water temperature with chiller stopped and chiller active, 1/2bar of hydraulic circuit pre-charge and considering only the water volume of the unit

\* For the configuration DPH (double pump P5) the chiller width will be 1305mm

\*\* For the configurations DP or DPH (double pump P3 or double pump P5) the chiller width will be 1305mm

**Air-cooled liquid chillers ENR series, rotary / scroll compressors, R410A / R32 / R454B refrigerant, brazed plate / coaxial / shell and tube evaporator, condenser coil with copper tubes and aluminium fins, AC axial fans. IP54 protection rating, chillers suitable for outdoor installation. Inbuilt water storage tank and single pump P3 as standard. 60Hz version as option.**

Type of available evaporators: CX = HITEMA coaxial evaporator, convoluted tube in tube exchanger installed inside the water storage tank ST = shell and tube evaporator, with high thickness copper tubes (0,41mm) B-ES = stainless steel brazed plate evaporator	Type of available expansion elements CP = Capillary tube VTS = Thermostatic expansion valve ETS = Electronic expansion valve (available as option)
--	---

**TECHNICAL DATA**

<b>PERFORMANCES</b>		Model	012	016	018	022	025	030	038	045
NOMINAL COOLING CAPACITY	W12°C/7°C @ 35°C (1)	kW	12,2	13,5	18,0	22,0	25,0	31,0	37,0	45,0
TOTAL NOMINAL ABSORBED POWER		kW	5,4	6,7	7,5	8,8	9,9	11,1	15,3	16,0
EER		kW/kW	2,76	2,36	2,76	2,93	2,90	3,15	2,82	3,25
SEPR (HT) (3)		-	4,72	4,51	4,66	4,88	4,91	5,11	4,59	5,28
NOMINAL WATER FLOW		m3/h	2,1	2,3	3,1	3,8	4,3	5,3	6,4	7,7
MECHANICAL MODE PRESSURE DROPS (4) (5) (6)		kPa	27	28	28	31	42	34	34	39
<b>FRIGORIFIC SECTION</b>										
COMPRESSORS / REFRIGERATING CIRCUITS / PARTITION STEP	nr.	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1	1/1/1
KIND OF COMPRESSOR	-	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL
KIND OF EVAPORATOR	-	CX	CX	CX	CX	CX	CX	CX	CX	CX
KIND OF EXPANSION ELEMENT	-	VTS	VTS	VTS	VTS	VTS	VTS	VTS	VTS	VTS
<b>HYDRAULIC SECTION</b>										
WATER FLOW RANGE (6)	m3/h	1,2÷2,9	1,2÷2,9	2,5÷5,0	3,0÷6,0	3,0÷6,0	4,0÷6,0	5,0÷12,0	6,0÷12,0	
MAXIMUM PUMP ABSORBED POWER (WP OR OPTION DP)	P3 (2)	kW	0,98	0,98	0,98	1,28	1,28	1,28	2,20	2,20
MAXIMUM PUMP ABSORBED CURRENT (WP OR OPTION DP)		A	1,78	1,78	1,78	2,37	2,37	2,37	4,24	4,24
MAXIMUM PUMP ABSORBED POWER (OPTION PH OR DPH)	P5 (2)	kW	1,10	1,10	1,47	1,47	1,47	1,47	2,94	2,94
MAXIMUM PUMP ABSORBED CURRENT (OPTION PH OR DPH)		A	2,17	2,17	2,86	2,86	2,86	2,32	5,83	5,83
HYDRAULIC CONNECTIONS (THREADED / FLANGED)	BSP / DN	1"	1"	1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	
TANK VOLUME (5) (8)	dm³	50	50	110	110	110	270	270	270	
EXPANSION VESSEL VOLUME (OPTION XV) (9)	liters	5	5	8	8	8	8	8	8	
<b>FAN SECTION (AXIAL)</b>										
FANS	nr.	1	1	1	1	1	2	2	2	
FAN SPEED REGULATION	-	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	
MAXIMUM FANS ABSORBED POWER	AC	kW	0,49	0,49	0,68	0,81	0,81	1,44	1,62	1,44
MAXIMUM FANS ABSORBED CURRENT		A	2,40	2,40	3,00	1,50	1,50	2,82	3,08	2,82
TOTAL AIR FLOW	m3/h	4750	4750	6500	6800	6800	16000	16400	15000	
<b>TOTAL ELECTRIC DATA</b>										
ELECTRICAL FEED	V/ph/Hz	400/3/50/N	400/3/50/N	400/3/50/N	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	
MAXIMUM ABSORBED CURRENT (F.L.A) (6)	A	13,3	13,9	18,8	19,8	21,1	24,4	31,8	37,1	
MAXIMUM PEAK CURRENT (L.R.A) (6)	A	71,0	71,0	75,0	104,0	127,4	120,4	144,2	178,2	
MAXIMUM PEAK CURRENT WITH SOFT START (OPTION SF) (L.R.A) (6)	A	NA	NA	NA	NA	NA	NA	NA	NA	
<b>NOISE DATA</b>										
SOUND PRESSURE FOR STANDARD CONFIGURATION (6) (7)	dB(A)	52,2	52,2	53,3	55,8	55,4	55,3	57,5	55,8	
SOUND PRESSURE FOR LOW NOISE CONFIGURATION (OPTION LNJ) (6) (7)	dB(A)	NA	NA	NA	NA	NA	54,3	57,2	54,5	
<b>DIMENSIONS AND WEIGHT</b>										
LENGTH	mm	820	820	1010	1010	1010	1610	1610	1610	
WIDTH	mm	615	615	720	720	720	860	860	860	
HEIGHT	mm	1415	1415	1585	1585	1585	1550	1550	1550	
WEIGHT EMPTY FOR STANDARD CONFIGURATION (5) (6)	kg	170	175	210	250	250	375	390	410	
WEIGHT OPERATIVE FOR STANDARD CONFIGURATION (5) (6)	kg	220	225	340	380	380	675	690	710	

The manufacturer reserves the right to modify specifications without notice. Last update: 27/01/2021  
Revision: 01-2021

- Data referred to:
- (1) Data referred to inlet/outlet water temperature = +12/+7 °C, ambient temperature = +35°C, fluid = Water
  - (2) Available pressure can be calculated from Hitema Online Selection Software
  - (3) SEPR: data comply with the European Regulation (EU) 2016/2281, referring to high temperature process chillers
  - (4) Pressure drops taken in account: evaporator, valves, piping
  - (5) Data referred to standard chiller configuration as indicated in frigorific section, with different evaporator this data can change
  - (6) Data referred to standard chiller configuration WP (single pump P3) and AC fans
  - (7) Sound pressure level referred to measures according to normative ISO3744, pressure level at distance of 10 m, referred to free field on reflecting surface
  - (8) To avoid excessive start/stop of the compressors a minimum water volume for the entire plant must be guarantee, the tank supplied by Hitema can be not enough
  - (9) The expansion vessel volume is calculated considering 40°C of deltaT between water temperature with chiller stopped and chiller active, 1/2bar of hydraulic circuit pre-charge and considering only the water volume of the unit

\* For the configuration DPH (double pump P5) the chiller width will be 1305mm  
 \*\* For the configurations DP or DPH (double pump P3 or double pump P5) the chiller width will be 1305mm

**Air-cooled liquid chillers ENR series, rotary / scroll compressors, R410A / R32 / R454B refrigerant, brazed plate / coaxial / shell and tube evaporator, condenser coil with copper tubes and aluminium fins, AC axial fans. IP54 protection rating, chillers suitable for outdoor installation. Inbuilt water storage tank and single pump P3 as standard. 60Hz version as option.**

Type of available evaporators:

CX = HITEMA coaxial evaporator, convoluted tube in tube exchanger installed inside the water storage tank

ST = shell and tube evaporator, with high thickness copper tubes (0,41mm)

B-ES = stainless steel brazed plate evaporator

Type of available expansion elements

CP = Capillary tube

VTS = Thermostatic expansion valve

ETS = Electronic expansion valve (available as option)

**TECHNICAL DATA**

**PERFORMANCES**

	Model	055	061	070	075	090	100	130	160
NOMINAL COOLING CAPACITY	kW	55,0	61,0	67,0	72,0	88,0	100,0	115,0	150,0
TOTAL NOMINAL ABSORBED POWER	kW	21,1	21,4	25,7	28,8	31,6	35,5	44,0	56,0
EER	kW/kW	2,91	3,23	2,89	2,74	3,03	3,03	2,92	2,92
SEPR (HT) (3)	-	4,80	5,01	4,78	4,75	4,91	5,01	5,02	4,59
NOMINAL WATER FLOW	m <sup>3</sup> /h	9,4	10,5	11,5	12,4	15,1	17,2	19,8	25,8
MECHANICAL MODE PRESSURE DROPS (4) (5) (6)	kPa	51	23	20	20	28	39	54	54

**FRIGORIFIC SECTION**

COMPRESSORS / REFRIGERATING CIRCUITS / PARTITION STEP	nr.	1/1/1	2/1/2	2/1/2	2/1/2	2/1/2	2/1/2	4/2/4	4/2/4
KIND OF COMPRESSOR	-	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL
KIND OF EVAPORATOR	-	CX	CX	CX	CX	CX	CX	ST	ST
KIND OF EXPANSION ELEMENT	-	VTS	VTS	VTS	VTS	VTS	VTS	VTS	VTS

**HYDRAULIC SECTION**

WATER FLOW RANGE (6)	m <sup>3</sup> /h	6,0÷12,0	8,0÷18,0	10,0÷20,0	10,0÷20,0	10,0÷20,0	10,0÷20,0	14,0÷27,0	15,4÷30,8	
MAXIMUM PUMP ABSORBED POWER (WP OR OPTION DP)	P3 (2)	kW	2,20	2,53	2,53	2,53	2,53	2,53	4,56	4,56
MAXIMUM PUMP ABSORBED CURRENT (WP OR OPTION DP)		A	4,24	4,56	4,56	4,56	4,56	4,56	7,75	7,75
MAXIMUM PUMP ABSORBED POWER (OPTION PH OR DPH)	P5 (2)	kW	2,94	6,12	6,12	6,12	6,12	6,12	10,20	10,20
MAXIMUM PUMP ABSORBED CURRENT (OPTION PH OR DPH)		A	5,83	10,40	10,40	10,40	10,40	10,40	17,40	17,40
HYDRAULIC CONNECTIONS (THREADED / FLANGED)	BSP / DN	1 1/2"	2"	2"	2"	2"	2"	DN65	DN65	
TANK VOLUME (5) (8)	dm <sup>3</sup>	270	410	410	410	410	410	390	390	
EXPANSION VESSEL VOLUME (OPTION XV) (9)	liters	8	12	12	12	12	12	19	19	

**FAN SECTION (AXIAL)**

FANS	nr.	2	2	2	2	2	2	2	3
FAN SPEED REGULATION	-	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF	ON/OFF
MAXIMUM FANS ABSORBED POWER	AC	kW	1,62	2,50	3,88	3,88	3,88	3,88	5,82
MAXIMUM FANS ABSORBED CURRENT		A	3,08	4,96	7,80	7,80	7,80	7,80	11,70
TOTAL AIR FLOW	m <sup>3</sup> /h	15600	25000	36000	36000	34000	32000	40000	57000

**TOTAL ELECTRIC DATA**

ELECTRICAL FEED	V/ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50
MAXIMUM ABSORBED CURRENT (F.L.A) (6)	A	43,8	48,0	56,1	61,4	72,4	78,8	92,4	117,5
MAXIMUM PEAK CURRENT (L.R.A) (6)	A	229,2	146,7	171,6	176,9	216,4	267,4	191,2	233,0
MAXIMUM PEAK CURRENT WITH SOFT START (OPTION SF) (L.R.A) (6)	A	NA	123,1	143,6	148,9	181,6	222,4	167,6	205,0

**NOISE DATA**

SOUND PRESSURE FOR STANDARD CONFIGURATION (6) (7)	dB(A)	58,8	57,6	59,2	59,3	59,5	60,3	59,5	61,1
SOUND PRESSURE FOR LOW NOISE CONFIGURATION (OPTION LNJ) (6) (7)	dB(A)	57,6	57,2	58,8	58,9	58,9	59,2	58,9	60,5

**DIMENSIONS AND WEIGHT**

LENGTH	mm	1610	2220	2220	2220	2220	2220	3355	3355
WIDTH	mm	860	1100	1100	1100	1100	1100	1105*	1105*
HEIGHT	mm	1550	2120	2120	2120	2120	2120	2205	2205
WEIGHT EMPTY FOR STANDARD CONFIGURATION (5) (6)	kg	500	740	765	770	785	890	1190	1260
WEIGHT OPERATIVE FOR STANDARD CONFIGURATION (5) (6)	kg	800	1160	1185	1190	1205	1310	1610	1695

The manufacturer reserves the right to modify specifications without notice.

Last update: 27/01/2021  
Revision: 01-2021

Data referred to:

(1) Data referred to inlet/outlet water temperature = +12/+7 °C, ambient temperature = +35°C, fluid = Water

(2) Available pressure can be calculated from Hitema Online Selection Software

(3) SEPR: data comply with the European Regulation (EU) 2016/2281, referring to high temperature process chillers

(4) Pressure drops taken in account: evaporator, valves, piping

(5) Data referred to standard chiller configuration as indicated in frigorific section, with different evaporator this data can change

(6) Data referred to standard chiller configuration WP (single pump P3) and AC fans

(7) Sound pressure level referred to measures according to normative ISO3744, pressure level at distance of 10 m, referred to free field on reflecting surface

(8) To avoid excessive start/stop of the compressors a minimum water volume for the entire plant must be guarantee, the tank supplied by Hitema can be not enough

(9) The expansion vessel volume is calculated considering 40°C of deltaT between water temperature with chiller stopped and chiller active, 1/2bar of hydraulic circuit pre-charge and considering only the water volume of the unit

\* For the configuration DPH (double pump P5) the chiller width will be 1305mm

\*\* For the configurations DP or DPH (double pump P3 or double pump P5) the chiller width will be 1305mm

**Air-cooled liquid chillers ENR series, rotary / scroll compressors, R410A / R32 / R454B refrigerant, brazed plate / coaxial / shell and tube evaporator, condenser coil with copper tubes and aluminium fins, AC axial fans. IP54 protection rating, chillers suitable for outdoor installation. Inbuilt water storage tank and single pump P3 as standard. 60Hz version as option.**

Type of available evaporators: CX = HITEMA coaxial evaporator, convoluted tube in tube exchanger installed inside the water storage tank ST = shell and tube evaporator, with high thickness copper tubes (0,41mm) B-ES = stainless steel brazed plate evaporator	Type of available expansion elements CP = Capillary tube VTS = Thermostatic expansion valve ETS = Electronic expansion valve (available as option)
--	---

TECHNICAL DATA									
PERFORMANCES		Model	185	200	230	280	340	370	430
NOMINAL COOLING CAPACITY	W12°C/7°C @ 35°C (1)	kW	170,0	204,3	227,0	277,0	319,0	365,0	410,0
TOTAL NOMINAL ABSORBED POWER		kW	62,8	71,3	84,8	103,2	115,8	129,8	146,8
EER		kW/kW	2,92	3,24	2,97	2,92	2,97	3,05	3,00
SEPR (HT) (3)		-	4,94	5,45	4,87	4,84	4,94	5,14	5,07
NOMINAL WATER FLOW		m3/h	29,2	35,1	39,0	47,6	54,8	62,7	70,4
MECHANICAL MODE PRESSURE DROPS (4) (5) (6)		kPa	55	38	56	56	48	55	61
<b>FRIGORIFIC SECTION</b>									
COMPRESSORS / REFRIGERATING CIRCUITS / PARTITION STEP	nr.	4/2/4	4/2/4	4/2/4	4/2/4	4/2/4	4/2/4	4/2/4	4/2/4
KIND OF COMPRESSOR	-	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL
KIND OF EVAPORATOR	-	ST	ST	ST	ST	ST	ST	ST	ST
KIND OF EXPANSION ELEMENT	-	VTS	VTS	VTS	VTS	VTS	VTS	VTS	VTS
<b>HYDRAULIC SECTION</b>									
WATER FLOW RANGE (6)	m3/h	17,5÷35,0	25,0÷46,0	25,0÷46,0	31,0÷58,0	38,0÷70,0	45,0÷80,0	52,0÷100,0	
MAXIMUM PUMP ABSORBED POWER (WP OR OPTION DP)	P3 (2)	kW	4,56	8,30	8,30	8,30	8,30	10,20	10,20
MAXIMUM PUMP ABSORBED CURRENT (WP OR OPTION DP)		A	7,75	14,10	14,10	14,10	14,10	17,40	17,40
MAXIMUM PUMP ABSORBED POWER (OPTION PH OR DPH)	P5 (2)	kW	10,20	16,22	16,22	16,22	16,22	16,22	19,94
MAXIMUM PUMP ABSORBED CURRENT (OPTION PH OR DPH)		A	17,40	26,60	26,60	26,60	26,60	26,60	32,70
HYDRAULIC CONNECTIONS (THREADED / FLANGED)	BSP / DN	DN65	DN80	DN80	DN100	DN100	DN100	DN125	
TANK VOLUME (5) (8)	dm³	390	390	500	500	500	500	500	
EXPANSION VESSEL VOLUME (OPTION XV) (9)	liters	19	19	19	19	19	19	19	
<b>FAN SECTION (AXIAL)</b>									
FANS	nr.	3	4	5	5	5	6	6	
FAN SPEED REGULATION	-	ON/OFF	CUT PHASE	CUT PHASE	CUT PHASE	CUT PHASE	CUT PHASE	CUT PHASE	CUT PHASE
MAXIMUM FANS ABSORBED POWER	AC	kW	5,82	7,76	9,70	9,70	9,70	11,64	11,64
MAXIMUM FANS ABSORBED CURRENT		A	11,70	15,60	19,50	19,50	19,50	23,40	23,40
TOTAL AIR FLOW	m3/h	54000	68800	91000	90000	85000	102000	96000	
<b>TOTAL ELECTRIC DATA</b>									
ELECTRICAL FEED	V/ph/Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50	
MAXIMUM ABSORBED CURRENT (F.L.A) (6)	A	139,5	162,6	179,4	212,0	241,4	278,0	307,0	
MAXIMUM PEAK CURRENT (L.R.A) (6)	A	283,5	351,1	367,9	439,4	492,1	528,7	641,2	
MAXIMUM PEAK CURRENT WITH SOFT START (OPTION SF) (L.R.A) (6)	A	248,7	306,1	322,9	385,0	430,1	466,7	559,6	
<b>NOISE DATA</b>									
SOUND PRESSURE FOR STANDARD CONFIGURATION (6) (7)	dB(A)	61,4	63,1	64,3	65,7	65,7	66,1	67,5	
SOUND PRESSURE FOR LOW NOISE CONFIGURATION (OPTION LNJ) (6) (7)	dB(A)	60,6	62,0	63,1	63,7	63,7	64,4	65,1	
<b>DIMENSIONS AND WEIGHT</b>									
LENGTH	mm	3355	4355	5350	5350	5350	6350	6350	
WIDTH	mm	1105*	1105**	1105	1105	1105	1105	1105	
HEIGHT	mm	2205	2205	2205	2205	2205	2205	2205	
WEIGHT EMPTY FOR STANDARD CONFIGURATION (5) (6)	kg	1320	1815	2105	2240	2415	2745	2810	
WEIGHT OPERATIVE FOR STANDARD CONFIGURATION (5) (6)	kg	1760	2275	2660	2800	2995	3345	3420	

The manufacturer reserves the right to modify specifications without notice.

Last update: 27/01/2021  
Revision: 01-2021

Data referred to:

- (1) Data referred to inlet/outlet water temperature = +12/+7 °C, ambient temperature = +35°C, fluid = Water
- (2) Available pressure can be calculated from Hitema Online Selection Software
- (3) SEPR: data comply with the European Regulation (EU) 2016/2281, referring to high temperature process chillers
- (4) Pressure drops taken in account: evaporator, valves, piping
- (5) Data referred to standard chiller configuration as indicated in frigorific section, with different evaporator this data can change
- (6) Data referred to standard chiller configuration WP (single pump P3) and AC fans
- (7) Sound pressure level referred to measures according to normative ISO3744, pressure level at distance of 10 m, referred to free field on reflecting surface
- (8) To avoid excessive start/stop of the compressors a minimum water volume for the entire plant must be guarantee, the tank supplied by Hitema can be not enough
- (9) The expansion vessel volume is calculated considering 40°C of deltaT between water temperature with chiller stopped and chiller active, 1/2bar of hydraulic circuit pre-charge and considering only the water volume of the unit

\* For the configuration DPH (double pump P5) the chiller width will be 1305mm

\*\* For the configurations DP or DPH (double pump P3 or double pump P5) the chiller width will be 1305mm